
# SPECIFICATION SHEET



# **MODELS 502 & 503 UTILITY VENTILATION FANS -**SIDE DISCHARGE



#### Efficient, high-performance ventilation for a variety of wall or ceiling installations.

## FEATURES

- GRILLE:
- · Contemporary styled grille complements modern decor
- White polymeric grilles can be painted to match any decor
- Aluminum filter available (purchase separately model 99010042) MOTOR.
- Motor assembly offers fast, easy "twist-lock" installation
- Permanently lubricated, thermally protected, plug-in motor
- Specially designed fan blade stays in balance will not distort
- Model 502 Fan blade 10" (254 mm) diameter, Model 503 - Fan blade 8" (203.2 mm) diameter HOUSING:
- · Installs easily in walls or ceiling
- · Steel housing 25 gauge finished with rugged electrically bonded epoxy paint
- Built-in back draft damper

#### **TYPICAL SPECIFICATION**

Ventilator shall be Broan Model 502 or 503.

Ventilator shall have compact steel housing finished with electrically-bonded epoxy paint. Grille to be white polymeric.

Motor assembly shall be removable and permanently lubricated. RPM shall not exceed 1600 (Model 502), 1725 (Model 503).

Model 503 is CSA certified for kitchen use when used with aluminum filter (purchased separately).

Air delivery shall be no less than 270 CFM (127.4 L/s) and sound levels no greater than 8.0 Sones (Model 502 -160 CFM (75.5 L/s) and Model 503 - 5.0 Sones). All air and sound ratings shall be certified by HVI. Units shall be CSA certified.

### **SPECIFICATIONS**

• Fits 3¼" x 10" (82.6 mm x 254 mm) duct							CFM	DUCT	
<ul> <li>Adjustable mounting brackets span from 14" (355.6 mm) to 24" (609.6 mm)</li> </ul>		MODEL	VOLTS	AMPS	RPM	SONES	(L/s)	(ROUND)	
3-1/4"	3-1/4"	502	120	1.7	1600	8	270 (127)	3-1/4" x 10" (82.6mm x 254mm)	
(82.5mm)	(80.6mm)	503	120	1.8	1725	5	160 (76)	3-1/4" x 10" (82.6mm x 254mm)	
16-3/4" (425.5mm) MODEL 502 HOUSING 502 GRILLE 502 GRILLE							502		
13-1/2" MODEL 502 (342.9mm) SOUARE	HOUSING SC (292	.1mm) UARE			<b>9.</b> 50			+++	
HOUSING					1SS 0.40		$\mathbb{N}$	+++	
503 GRILLE									
502 GRILLE									
TESTED/CERTIFIED HVI-2100 CERTIFIED RATINGS comply with the new testing technologies and procedures prescribed									
2100 V Forduct performance is rated at 0.1 in. static ressure, based on tests conducted in AMCA's state-of-									
the art laboratory. Sones are a measure of humanly produced loudness, based on laboratory meas- urements.					e Air Flow Rate (cfm)				
Home Ventilating Institute									
Broan-NuTone LLC, Hartford, Wisconsin U.S.A. 53027									
Broan-NuTone Canada Inc., Mississauga, Ontario, Canada L5T 1H9									
REFERENCE QTY.	REMARKS			Project					
				Location	1 <u> </u>				
				Architect					
				Engineer					
				Contrac	tor				
				Submitted by Date					

\*PRODUCT SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

502d031023