


Submittal Data Information

301-003

1600 Series Pumps (1615 Custom Model)

EFFECTIVE: November 16, 2016		SUPERS	SEDES: September	1750 RPM MODEL 1615		
JOB						
CONTRACTOR			REP.			
ITEM NO.	MODEL NO.	IMPELLER DIA.	G.P.M.	T.D.H.	H.P.	ELEC. CHAR.
NSF 61 Certified Yes No				WEIGHT	PUMP/MOT	OR



DIMENSIONS:

* 1/3 HP AVAILABLE IN 1 PHASE ONLY

CUSTOM MODEL	FLANGE	POWER	DIMENSIONS			
NUMBER	SIZE	HP (KW)	Α	В	С	D
1615	1½ (38)	1/3 (0.25) *	31/8 (79)	18.0 (457)	- 13½ (343)	16½ (410)
		1/2 (0.37)		18.5 (470)		
		³ / ₄ (0.56)		19.0 (483)		
		1 (0.75)		19.5 (495)		

English dimensions are in inches. Metric dimensions are in millimeters. Metric data is presented in (). Do not use for construction purposes unless certified.

MATERIALS OF CONSTRUCTION


Item Standard		Optional		
Casing	Cast Iron	304 Stainless Steel		
Impeller	304 Stainless Steel	N/A		
Shaft	Hardened Alloy Steel	Stainless Steel 416		
Shaft Sleeve	Cupro-Nickel	N/A		
Bracket	Cast Iron	Cast Iron with Stainless Steel Face Plate		

N/A - Not Available

SPECIFICATIONS

MOTORS	1750 RPM, Three Phase 200V or 230/460V, 60Hz. Also available in Single Phase with overload protection except 3HP (2238 Watts).		
BODY	Flanged in-line connections. Companion flanges are included.		
FLANGES	Flanges are tapped for gauges (1/4" NPT).		
IMPELLER	Closed, dynamically balanced		
DRIVE COUPLING	Non-Metallic, vibration dampening		
FRAME	Ball bearing type, permanently lubricated. REMOVABLE BEARING CARTRIDGE FITS ALL MODELS.		
MECHANICAL SEAL	Type 21 2 Piece Standard – 250°F (121°C) Operating Temperature or Optional High Temperature – 300°F (149°C) Operating Temperature		
WORKING PRESSURE	175 PSI (1207 kpa). In accordance with ANSI Standard B16.1.		

MODEL 1615 CUSTOM UNIT PERFORMANCE CURVE (1750 RPM)



Comments:



