

ENERGY EFFICIENT SINGLE SPEED FULL RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
345212	CHII-NI-1/2FE	115/208-230	8.8/4.5-4.4	1/2	1.90	0.95	UL1, NSF ²	2" x 2"	41	G
345213	CHII-NI-3/4FE	115/208-230	11.2/6.0-5.6	3/4	1.67	1.25	UL1, NSF ² , CSA ³	2" x 2"	43	H
345205	CHII-NI-1FE	115/208-230	14.8/7.8-7.4	1	1.65	1.65	UL1, NSF ²	2" x 2"	46	I
345206	CHII-NI-1-1/2FE	208-230	9.6-8.8	1-1/2	1.47	2.20	UL1, NSF ²	2" x 2"	54	J
345208	CHII-NI-2FE	208/230	11.0-10.2	2	1.30	2.60	UL1, NSF ²	2" x 2"	55	K
345209	CHII-NI-3FE	208-230	15.0-13.6	3	1.15	3.45	UL1, NSF ²	2" x 2"	56	L

ENERGY EFFICIENT SINGLE SPEED UP RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
346209	CHII-NI-2-1/2AE	208-230	11.0-10.2	2-1/2	1.04	2.60	UL ¹	2" x 2"	55	K

STANDARD EFFICIENCY SINGLE SPEED FULL RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
345202	CHI-NI-1/2F	115/230	10.8/5.4	1/2	1.90	0.95	UL1, NSF ² , CSA ³	2" x 2"	41	G
345203	CHII-NI-3/4F	115/230	14.2/7.1	3/4	1.67	1.25	UL1, NSF ² , CSA ³	2" x 2"	41	H
345204	CHII-NI-1F	115/230	16.0/8.0	1	1.65	1.65	UL1, NSF ² , CSA ³	2" x 2"	41	I
345201	CHII-NI-1-1/2F	115/230	22.4/11.2	1-1/2	1.50	2.20	UL1, NSF ²	2" x 2"	49	J
345218	CHII-NI-2F	230	11.5	2	1.30	2.60	UL1, NSF ² , CSA ³	2" x 2"	55	K
345219	CHII-NI-3F	230	14.1	3	1.15	3.45	UL1, NSF ²	2" x 2"	56	L

STANDARD EFFICIENCY SINGLE SPEED UP RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ⁴	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
346203	CHII-NI-3/4A	115/230	10.8/5.4	3/4	1.25	0.94	UL1, CSA ²	2" x 2"	41	G
346204	CHII-NI-1A	115/230	14.2/7.1	1	1.25	1.25	UL1, CSA ²	2" x 2"	41	H
346206	CHII-NI-1-1/2A	115/230	16.0/8.0	1-1/2	1.10	1.65	UL1, CSA ²	2" x 2"	41	I
346201	CHII-NI-2A	115/230	22.4/11.2	2	1.10	2.20	UL1, CSA ²	2" x 2"	49	J
346249	CHII-NI-2-1/2A	230	11.5	2-1/2	1.04	2.60	UL ¹	2" x 2"	55	K

ENERGY EFFICIENT SINGLE SPEED FULL RATED - 3 PHASE

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
345290	CHII-NI-3/4FE, 3PH	208-230/430	3.8-3.6/1.8	3/4	1.65	1.25	2" x 2"	43	H
345284	CHII-NI-1FE, 3PH	208-230/460	5.0-4.6/2.3	1	1.65	1.65	2" x 2"	48	I
345286	CHII-NI-1-1/2FE, 3PH	208-230/460	6.4-5.8/2.9	1-1/2	1.47	2.20	2" x 2"	49	J
345288	CHII-NI-2FE, 3PH	208-230/460	7.1-6.8/3.4	2	1.30	2.60	2" x 2"	55	K
345299	CHII-NI-3FE, 3PH	208-230/460	11.0-10.4/5.2	3	1.15	3.45	2" x 2"	55	L

1: 'UL' indicates that pump bears a specific UL mark signifying evaluation to U.S. Standards UL1081 for Permanently Connected Swimming Pool and Spa Pumps and to Canadian Standards CAN/CSA C22.2 No. 108-01 Liquid Pumps for Swimming Pools and Spas. (Enclosure 3).

2: 'NSF' indicates that pump bears a NSF mark signifying evaluation to NSF Standard 50 for Self-Priming Centrifugal Pumps for Swimming Pools, Spas and Hot Tubs.

3: 'CSA' indicates that pump bears a CSA mark signifying evaluation to Canadian Standards CAN/CSA C22.2 No. 108-01 Liquid Pumps for Swimming Pools and Spas. (Enclosure 3).

4: Product may have been evaluated to other state and local regulatory standards. Listing status may change. Always confirm status with appropriate if in doubt.