

## ENERGY EFFICIENT SINGLE SPEED FULL RATED

Product	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications <sup>3</sup>	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
MPE6C-204L	115/230	11.0/5.5	1/2	1.90	0.95	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	37	D
MPE6D-205L	115/230	13.8/6.9	3/4	1.65	1.25	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	39	E
MPE6E-206L	115/230	16.0/8.0	1	1.65	1.65	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	44	F
MPE6F-207L	230	10.4	1-1/2	1.47	2.20	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	51	G
MPE6G-208L	230	11.2	2	1.30	2.60	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	54	H

## ENERGY EFFICIENT SINGLE SPEED UP RATED

Product	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications <sup>3</sup>	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
MPEA6D-204L	115/230	11.0/5.5	3/4	1.27	0.95	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	37	D
MPEA6E-205L	115/230	13.8/6.9	1	1.25	1.25	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	39	E
MPEA6F-206L	115/230	16.0/8.0	1-1/2	1.10	1.65	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	44	F
MPEA6G-207L	230	10.4	2	1.10	2.20	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	51	G
MPEAA6G-208L	230	11.2	2-1/2	1.04	2.60	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	54	H

## STANDARD EFFICIENCY SINGLE SPEED UP RATED

Product	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications <sup>3</sup>	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
MPRA6D-204L	115/230	13.4/6.7	3/4	1.27	0.95	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	35	D
MPRA6E-205L	115/230	15.3/7.6	1	1.25	1.25	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	37	E
MPRA6F-206L	115/230	19.2/9.6	1-1/2	1.10	1.65	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	42	F
MPRA6G-207L	230	12	2	1.10	2.20	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	49	G

## ENERGY EFFICIENT TWO SPEED 3450 RPM, LOW SPEED 1725 RPM UP RATED

Product	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications <sup>3</sup>	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
MPEA6YG-207L	230	10.1/3.7	2	1.10	2.20	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	53	B, G
MPEA6YG-208L	230	11.9/3.5	2-1/2	1.04	2.60	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	57	C, H

## STANDARD EFFICIENCY TWO SPEED 3450 RPM, LOW SPEED 1725 RPM UP RATED

Product	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications <sup>3</sup>	Port Size (NPT)	Carton Wt (Lbs)	Curve Key
MPRA6YF-206L	230	9.2/2.5	1-1/2	1.10	1.65	UL <sup>1</sup> , NSF <sup>2</sup>	2" x 2"	45	A, F

1: "UL" indicates that pump bears a specific UL mark signifying evaluation to U.S. Standards UL1081 for Permanently Connected Swimming Pool and Spa Pumps and to Canadian Standards CAN/CSA C22.2 No. 108-01 Liquid Pumps for Swimming Pools Only (Enclosure 3).

2: "NSF" indicates that pump bears a NSF mark signifying evaluation to NSF Standard 50 for Self-Priming Centrifugal Pumps for Swimming Pools, Spas and Hot Tubs.

3: Product may have been evaluated to other state and local regulatory standards. Listing status may change. Always confirm status with appropriate agency if in doubt.