

ENERGY EFFICIENT SINGLE SPEED FULL RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt(Lbs)	Curve Key
011511	WFE-2	115/208-230	8.8/4.5-4.4	1/2	1.90	0.95	UL1, NSF2	2" x 2"	41	E
011512	WFE-3	115/208-230	11.2/6.0-5.6	3/4	1.67	1.25	UL1, NSF2	2" x 2"	41	F
011513	WFE-4	115/208-230	14.8/7.8-7.4	1	1.65	1.65	UL1, NSF2	2" x 2"	46	G
011514	WFE-6	208-230	9.6-8.8	1-1/2	1.47	2.20	UL1, NSF2	2" x 2"	54	H
011515	WFE-8	208-230	11.0-10.2	2	1.30	2.60	UL1, NSF2	2" x 2"	55	I
011516	WFE-12	208-230	15.0-13.6	3	1.15	3.45	UL1, NSF2	2" x 2"	56	J

ENERGY EFFICIENT SINGLE SPEED UP RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt(Lbs)	Curve Key
011517	WFE-24	115/208-230	11.2/6.0-5.6	1	1.25	1.25	UL1, NSF2	2" X 2"	41	F
011518	WFE-26	115/208-230	14.8/7.8-7.4	1-1/2	1.10	1.65	UL1, NSF2	2" X 2"	46	G
011519	WFE-28	208-230	9.6-8.8	2	1.10	2.20	UL1, NSF2	2" X 2"	54	H
011520	WFE-30	208-230	11.0/10.2	2-1/2	1.04	2.60	UL1, NSF2	2" X 2"	55	I

STANDARD EFFICIENCY SINGLE SPEED FULL RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt(Lbs)	Curve Key
011578	WF-2	115/230	10.5/5.4	1/2	1.95	0.95	UL1, NSF2	2" X 2"	41	E
011579	WF-3	115/230	14.2/7.1	3/4	1.67	1.25	UL1, NSF2	2" X 2"	41	F
011580	WF-4	115/230	16.0/8.0	1	1.65	1.65	UL1, NSF2	2" X 2"	46	G
011581	WF-6	115/230	22.4/11.2	1-1/2	1.5	2.20	UL1, NSF2	2" X 2"	54	H
011582	WF-8	230	11.5	2	1.30	2.60	UL1, NSF2	2" X 2"	55	I
011583	WF-12	230	14.1	3	1.15	3.45	UL1, NSF2	2" X 2"	56	J

STANDARD EFFICIENCY SINGLE SPEED UP RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt(Lbs)	Curve Key
011771	WF-23	115/230	10.8/5.4	3/4	1.24	0.95	UL1, NSF2	2" X 2"	41	E
011772	WF-24	115/230	14.2/7.1	1	1.24	1.25	UL1, NSF2	2" X 2"	41	F
011773	WF-26	115/230	16.0/8.0	1-1/2	1.10	1.65	UL1, NSF2	2" X 2"	46	G
011774	WF-28	115/230	22.4/11.2	2	1.10	2.20	UL1, NSF2	2" X 2"	54	H
011775	WF-30	230	11.5	2-1/2	1.04	2.60	UL1, NSF2	2" X 2"	55	I

THREE PHASE TEFC SUPER DUTY

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt(Lbs)	Curve Key
011641	WFK-4	208/230/460	4.9-4.5/2.3	1	1.65	1.65	NSF ²	2" X 2"	46	G
011642	WFK-6	208/230/460	6.4-6.3/3.2	1-1/2	1.47	2.21	NSF ²	2" X 2"	48	H
011643	WFK-8	208/230/460	7.5-7.2/3.6	2	1.30	2.60	NSF ²	2" X 2"	51	I
011644	WFK-12	208/230/460	9.8-9.4/4.7	3	1.15	3.45	NSF ²	2" X 2"	58	J

ENERGY EFFICIENT TWO SPEED 3450 RPM, LOW SPEED 1725 RPM FULL RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt(Lbs)	Curve Key
012530	WFDS-3	115	14.6/4.7	3/4	1.67	1.25	UL1, NSF ²	2" X 2"	42	A, F
011486	WFDS-4	230	7.8/3.0	1	1.65	1.65	UL1, NSF ²	2" X 2"	47	B, G
011522	WFDS-6	230	10.0/3.5	1-1/2	1.47	2.20	UL1, NSF ²	2" X 2"	55	C, H
011523	WFDS-8	230	11.0/4.0	2	1.30	2.60	UL1, NSF ²	2" X 2"	56	D, I

ENERGY EFFICIENT TWO SPEED 3450 RPM, LOW SPEED 1725 RPM UP RATED

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications ³	Port Size (NPT)	Carton Wt(Lbs)	Curve Key
012485	WFDS-24	115	14.6/4.7	1	1.25	1.25	UL1, NSF ²	2" x 2"	42	A, F
012518	WFDS-26	230	7.8/3.0	1-1/2	1.10	1.65	UL1, NSF ²	2" x 2"	47	B, G
011524	WFDS-28	230	10.0/3.5	2	1.10	2.20	UL1, NSF ²	2" x 2"	55	C, H
011525	WFDS-30	230	11.0/4.0	2-1/2	1.04	2.60	UL1, NSF ²	2" x 2"	56	D, I

ENERGY EFFICIENT SINGLE PHASE - 50Hz INPUT POWER FREQUENCY

Product	Model	Voltage	Full Load Amps	HP	SF	SFHP	Primary Listings and Certifications	Port Size (NPT)	Carton Wt (Lbs)
347926	WFEL-2	240/120	7.5/15.0	1/2	1.10	0.55	UL1, NSF ²	2 in. x 2 in.	41
347927	WFEL-3	240/120	7.5/15.0	3/4	1.10	0.83	UL1, NSF ²	2 in. x 2 in.	41
347928	WFEL-4	240/120	6.9/13.8	1	1.10	1.10	UL1, NSF ²	2 in. x 2 in.	46
347929	WFEL-6	240	7.2	1.5	1.10	1.65	UL1, NSF ²	2 in. x 2 in.	54
347930	WFEL-8	240	9.4	2	1.10	2.20	UL1, NSF ²	2 in. x 2 in.	55

1: 'UL' indicates that pump bears a UL mark signifying evaluation to U.S. Standards UL1081 for Permanently Connected Swimming Pool and Spa Pumps and to Canadian Standards CAN/CSA C22.2 No. 108-01 Liquid Pumps for Swimming Pools Only (Enclosure 3).
 2: 'NSF' indicates that pump bears a NSF mark signifying evaluation to NSF Standard 50 for Self-Priming Centrifugal Pumps for Swimming Pools, Spas and Hot Tubs.
 3: Product may have been evaluated to other state and local regulatory standards. Listing status may change. Always confirm status with appropriate agency if in doubt.