

**SERIES 200 IN-LINE COMMERCIAL SERVICE KITS
ENSEMBLES DE SERVICE POMPES EN-LIGNE SÉRIE 200**

REPLACEMENT POWERHEADS / TÊTES DE POMPES DE RECHANGES

Model/ Modele	Nominal Flange Size Grandeur Bride (inches/pcs)	Max. HP Max	PH	Voltage	Poids Shipping Weight (lbs)	Part Number/ No. Piec	Prix (\$) Sug. List Price (\$)	Disc. Code d'esc.
UMC50-40	2	1/5	1	115	22	91584868	1,420	UPP
			1	230	22	54552488	1,420	
UMC65-40	2 1/2	1/3	1	115	26	91584869	1,531	
			1	230	26	54652488	1,531	
			3	208	26	54652475	1,476	
			3	230	26	54652477	1,476	
UMC50-80	2	1/3	1	115	28	91584851	1,722	
			1	230	28	91584950	1,722	
			3	208	29	55552875	1,569	
			3	230	27	55552877	1,569	
UMC65-80	2 1/2	3/4	1	115	39	91584853	1,850	
			1	230	38	56652888	1,534	
			3	208	34	91584952	1,745	
			3	230	33	56652877	1,745	
UMC80-80	3	2/3	1	115	39	91584857	2,104	
			1	230	39	56852888	2,104	
			3	208	38	56852875	2,023	
			3	230	37	56852877	2,023	
UPC50-160	2	3/4	1	115	30	91584849	2,079	
			1	230	29	91584848	2,079	
			3	208	29	91584846	2,047	
			3	230	26	91584847	2,047	
UPC65-160	2 1/2	1 1/2	1	230	39	91584856	2,400	
			3	208	36	91584854	2,250	
			3	230	34	91584855	2,250	
			3	208	38	56853625	2,434	
UPC80-160	3	2	3	208	38	56853625	2,434	
			3	230	40	91584858	2,434	

REPLACEMENT POWERHEAD CONSISTS OF:

Stator, rotor terminal box, impeller, gaskets and attaching hardware.

POWERHEAD CAN BE USED IN:

Both open and closed systems.

* Single speed only. Requires external thermal motor protection. Model designation: "UMA" or "UPA"
Pump/motor on three speed units is standard without thermal protection (optional).