Model #SJC100-2

1 HP Dual Voltage Cast Iron Shallow Well Jet

Pump



Inlet	NPT 1 1/4					
Discharge	NPT1					
Pump Cover	/					
Motor Housing	ZL102					
Pump Body	HT200					
Switch Type	Press switch					
Impeller	PPO-GF30					
Seal Design	Mechanical seal					
Seal Material	Graphite & Ceramic					
Oil Filled Motor	No					
Power Cord	/					
Net Weight	20.9					
Gross Weight	26.5					
Package Size	17.7x12x10					
Expected Life Cycle	ON 2 sec. OFF 2 sec. 300,000 cycles					
Motor Wires	Copper					
Self-Priming	Yes					
Certification	cULus					

Features & Benefits: For use with shallow well within 25ft. Durable cast iron pump body.
Built-in automatic thermal overload protection.
Dual voltage motor (115/230V), Factory set for 115V.
 Pressure switch pre-set at 30-50 PSI. 1¼" NPT discharge and 1" NPT discharge.
 NET discharge and T NET discharge. NEMA Motor. 2 year warranty.

* 3 ye	ear v	varra	ntv.
--------	-------	-------	------

Model HP	UD			Discharge	GPH of water @ Total Ft. of Head				May Lload St	
	Voltage	AMP	NPT(In)	5 ft	10 ft	15 ft	20 ft	25 ft	Max.Head Ft	
SJC100-2	1	115 or 230	14/7	1	1260	1125	1010	895	705	164